



dimensions tolerance to be +/-0.2

UNLESS OTHERWISE SPECIFIED:					NAME	DATE	DO NOT SCALE DRAWING		REVISION		
<div>1.DO NOT SCALE DRAWING.</div> <div>2.INTERPRET PER ASME Y14.100M.</div> <div>3.DIMENSIONS ARE IN METRIC.</div> <div>4.SURFACE TEXTURE SHALL BE 125</div> <div>5.REMOVE BURRS AND SHARP EDGES</div> <div>6.DIMENSIONS APPLY BEFORE PLATING OR CONVERSION COATING.</div> <div>7.PARENTHETICAL DATA IS FOR REFERENCE ONLY</div>	TOLERANCES:						<div><div><div></div></div><div>AGILTRON</div><div>INC</div></div>				
	ON ALL HOLE DIAMETERS				DRAWN						
	Under 1.0	+0.05 -0.01	25 THRU 50	+0.2 -0.1	CHK'D						
	1.0 THRU 5.0	+0.1 -0.025	>50	+0.25 -0.1	APP'VD						
	5.0 THRU 10.0	+0.15 -0.025			MFG			TITLE: <div>Fast switch fiber to fiber</div>			
	10.0 THRU 25	+0.2 -0.025			Q.A						
	ON DECIMAL DIMENSIONS:		ON ANGULAR DIMENSIONS:		MATERIAL:			DWG NO.			
	.XXX +/-0.010		MACHINED +/-0°30'					A4			
.XX +/-0.03		LOCATING +/-0°30'									
.X +/-0.1		FORMED +/-1°									
		CHANFERS +/-5°		WEIGHT:			SCALE:2:1		SHEET 1 OF 1		